## **CLAIMS**

3047

10

 A method of retraining a trainable data classifier comprising the steps of:

providing a first item of training data;

comparing the first item of training data with a second item of training data already used to train the data classifier;

calculating a measure of conflict between the first and second items of training data;

- using the first item of training data to retrain the data classifier responsive to the measure of conflict.
- 2. A method according to claim 1 wherein the step of using the first item of training data is responsive to a predetermined conflict threshold value.
- 3. A method according to claim 2 wherein the threshold value is non-zero.
  - 4. A method according to claim 1 wherein the measure of conflict comprises a geometric difference between the first and second items of training data.
- 5. A method according to claim 4 wherein the geometric difference comprises a Euclidean distance.
- 6. A method according to claim 1 wherein the
  measure of conflict comprises an association
  coefficient of the first and second items of training
  data.

ť,n

100 mm

1.4

5

- 7. A method according to claim 6 wherein the association coefficient is a Jaccard's coefficient.
- 8. A method according to claim 7 wherein the measure of conflict is derived from a both a Euclidean distance between and a Jaccard's coefficient of the first and second items of training data.
- 9. A method according to claim 8 wherein the measure of conflict is derived from a Euclidean distance and a Jaccard's coefficient composed in an exponential relationship with respect to each other.
- 10. A method according to claim 8 wherein the measure of conflict is derived from a function of a Euclidean distance multiplied by an exponent of a function of the Jaccard's coefficient.
  - 11. A method according to claim 1 wherein the data classifier comprises a neural network.
  - 12. A method according to claim 1 wherein the training data comprises telecommunications network data.
    - 13. A method according to claim 1 wherein the training data comprises telecommunications call detail record data.
    - 14. A method of training a trainable data classifier comprising the steps of:

providing a plurality of items of training data;

comparing a first of the items of training

20

30

25

calculating a measure of conflict between the first and second items of training data;

using one of the first and second items of training data to retrain the data classifier responsive to the measure of conflict.

15. A apparatus for retraining a trainable data classifier and comprising:

an input port for receiving a first item of training data;

a comparator arranged to compare the first item of training data with a second item of training data already used to train the data classifier;

a calculator for calculating a measure of conflict between the training data; and

an output port arranged to output the first item of training data to the data classifier responsive to the measure of conflict.

- 16. A anomaly detection system comprising apparatus according to claim 15.
- 17. A telecommunications data anomaly detection system comprising apparatus according to claim 15.
  - 18. A telecommunications fraud detection

Crist.

5

15

20

25

30

35

1.3

5

15

20

system comprising apparatus according to claim 15.

- 19. An account fraud detection system comprising apparatus according to claim 15.
- 20. An apparatus for retraining a trainable data classifier comprising:

an input port for receiving a plurality of items of training data;

a comparator arranged to compare a first of the items of training data with a second of the items of training data;

a calculator for calculating a measure of conflict between the first and second items of training data;

an output port arranged to output the first item of training data to the data classifier responsive to the measure of conflict.

21. A program for a computer on a machine readable medium arranged to perform the steps of:

receiving a first item of training data;

comparing the first item of training data with a second item of training data already used to train the data classifier;

calculating a measure of conflict between the first and second items of training data;

using the first item of training data to retrain the data classifier responsive to the

35

30

measure of conflict.

22. A program for a computer on a machine readable medium arranged to perform the steps of:

5

receiving a plurality of items of training data;

. films

comparing a first of the items of training data with a second of the items of training data;

10

calculating a measure of conflict between the first and second items of training data; and

15

using one of the first and second items of training data to retrain the data classifier responsive to the measure of conflict.

:= :1

LEATER AMERICA STREET, ST. LEATER STREET, ST. LEATE